



Freedom Walk-in Tubs Comparison Charts (U shaped)

Compare Dimensions (U-Shape Door)			
	30" x 52" APWO3052H5P	32" x 52" APWO3252H5P	26" x 45" APWO2645H2P
Nominal size	52"L x 30"W	52"L x 32"W	45"L x 26"W
Seat width	20"	23"	20"
Seat length	14 1/2"	13 3/4"	14"
Interior length	43 3/4"	44 1/2"	38 7/8"
Seat to Overflow Top	17 1/4"	16 5/8"	18 1/2"
Seat to foot well	17"	17"	15"
Footwell	17"W x 15"L	19"W x 18"L	18" W x 14 1/4" L

Compare Specs (U-Shape Door)			
	30" x 52" APWO3052H5P	32" x 52" APWO3252H5P	26" x 45" APWO2645H2P
Gallons USA (Unoccupied)	85	105	75
Gallons USA (Occupied)	45-65	55-85	35-55
Suggested Water Heater*	75*	75*	65*
Approximate Drain Time	80 Seconds**	80 Seconds**	80 Seconds**
Drain/Door Location	Right or Left	Right or Left	Right or Left
Product Net Weight LBS	215***	220***	210***
Product Shipping Weight LBS	365***	385***	280***

- * Suggested water heater size for a household with only one single bather. A household with any additional bathers should consider the next size available water heater.
- ** Approximate drainage time is under ideal plumbing conditions, your drainage times may vary.
- *** Net and shipping weight depends on what package is ordered.



Freedom Walk-in Tubs Comparison Charts (U shaped)

Compare Features (U-Shaped Door)			
	30" x 52" APWO3052H5P	32" x 52" APWO3252H5P	26" x 45" APWO2645H2P
Grab Bar(s)	2	2	1
Hydro Jets	15	15	17
Air Jets (if added)	14	14	N/A
Number of Access Panels	2	2	2
One End Panel Included	1	1	1

Features for Different Jetting Options (U Shaped Door)					
	Hydro	Hydro + Air	Hydro + Foot	Hydro + Micro	Air + Hydro + Micro
Available Tub Options	30" x 52", 32" x 52", 26" x 45"	30" x 52", 32" x 52",	30" x 52", 32" x 52",	30" x 52", 32" x 52",	32" x 52"
Dedicated Outlet Requirements	1 GCFI 20 Amp 120 Volt	1 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt
Pumps	1	2	2	2	3
Outlet Receptacles Needed	2	2	3	3	2
Ozone	Yes	Yes	Yes	Yes	Yes
Inline heater	Yes	Yes	Yes	Yes	Yes
Autopurge	No	Yes	No	No	Yes
MicroBubbles	No	No	No	Yes	Yes
Push Button	Yes	Yes	Yes	Yes	Yes
Digital	No	Optional	No	No	Optional
LED	No	Yes	Yes	Yes	Yes
Heated Seat	Optional	Optional	Optional	Optional	Optional



Freedom Walk-in Tubs Comparison Charts (Transfer Tubs)

Compare Specs (Transfer)					
	Transfer26	Transfer30	Transfer32	Transfer60	TransferXXXL
Gallons USA (Unoccupied)	75	80	107	90	132
Gallons USA (Occupied)	35-55	35-65	45-65	55-75	65-85
Suggested Water Heater*	75*	75*	75*	75*	75*
Approximate Drain Time	80 Seconds	80 Seconds	80 Seconds	80 Seconds	120 Seconds
Drain/Door Location	Right or Left	Right or Left	Right or Left	Right or Left	Right or Left
Product Net Weight LBS	205	220	215	220	220
Product Shipping Weight LBS	300	366	373	300	300

* Suggested water heater size for a household with only one single bather. A household with any additional bathers should consider the next size available water heater.

Compare Dimensions (Transfer)					
	Transfer26	Transfer30	Transfer32	Transfer60	TransferXXXL
Nominal size	52"L x 26"W	52"L x 30"W	52"L x 32"W	60"L x 30"W	55"L x 36"W
Seat width	19"	22"	24"	22"	29"
Seat length	16 3/4"	15 3/4"	16 7/8"	18 1/2"	17 3/4"
Interior length	43 5/8"	43 3/4"	43 3/4"	50 3/4"	48 1/8"
Seat to Overflow Top	17 1/2"	18 1/2"	19 3/4"	19 5/8"	17 3/4"
Seat to Footwell	17"	17"	17"	17"	17"
Footwell	15 1/2"W x 17 1/2"L	18" W x 17"L	19 1/2"W x 17 1/2"L	17"W x 19"L	23"W x 18"L



Freedom Walk-in Tubs Comparison Charts (Transfer Tubs)

Compare Features (Transfer)					
	Transfer26	Transfer30	Transfer32	Transfer60	TransferXXXL
GrabBar(s)	2	2	2	2	2
Hydro Jets	13	13	13	13	13
Air Jets	17	17	17	17	16

Jetting Packages							
Jetting	Hydro	Hydro + Air	Hydro + Foot	Hydro + Micro	Air + Hydro + Micro	Air + Hydro + Foot	Air + Hydro + Foot + Micro
Available Tub Options	Transfer26, Transfer30, Transfer32, Transfer60, TransferXXXL	Transfer26, Transfer30, Transfer32, Transfer60, TransferXXXL	Transfer26, Transfer30, Transfer32, Transfer60, TransferXXXL	Transfer26, Transfer30, Transfer32, Transfer60, TransferXXXL	Transfer32, Transfer60, TransferXXXL	Transfer32, Transfer60, TransferXXXL	TransferXXXL
Dedicated Outlet Requirements	1 GCFI 20 Amp 120 Volt	1 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt	2 GCFI 20 Amp 120 Volt	3 GCFI 20 Amp 120 Volt
Pumps	1	2	2	2	3	3	4
Outlet Receptacles Needed	2	2	3	3	2	2	3
Ozone	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Inline heater	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Autopurge	No	Yes	No	No	Yes	Yes	Yes
MicroBubbles	No	No	No	Yes	Yes	No	Yes
Push Button	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Digital	No	Optional	No	No	Optional	Optional	Optional
LED	No	Yes	Yes	Yes	Yes	Yes	Yes
Heated Seat	Optional	Optional	Optional	Optional	Optional	Optional	Optional